

YAESU FT-DX5000MP LTD

**HF/50 MHz BASE TRANSCEIVER | OUTPUT 200 W | 220 VAC |
INCL. 300 HZ ROOFING FILTER**



The Yaesu FT-DX5000MP LTD HF/50 MHz 200 watt transceiver is a new premium class of Yaesu radios with two fully independent receivers plus many unique options and accessories designed to meet the performance requirements of even the most demanding amateur radio operator.

Yaesu engineers have achieved 112 dB dynamic range and an IP3 [3rd Order Intercept Point] of +40 dBm (CW, 500 Hz BW). Newly designed, extra sharp roofing filters for VFOA/Main receiver are selectable between 300 Hz, 600 Hz, 3 kHz, 6 kHz and 15 kHz. Yaesu incorporates two of their famous custom designed 32 bit floating point DSP chips based on the TI TMS320C6727B running at 300 MHz ... one for VFO A and one for VFO B. Enjoy state of the art on the transmit side with a pair of reliable VRF150 FETS in a push-pull configuration yielding 200 watts (75 watts class A operation).

Three electro-luminescent subdisplays indicate sub frequency, graphical wave and menu functions. The rear panel features a 9 MHz IF out from VFO Main receiver. Other enhancements include: large multi-function meter and variable CW audio peak filter. Shown above with SM-5000 Station Monitor which is not included.

Features

- 6-160 m
- Electronic Keyer
- Variable RF Filter (160-10M)
- Parametric Microphone Equalizer
- Dual Receive In Band Function
- Contest-ready Antenna Selection
- Manual and Automatic Digital Notch
- Electro-Luminescent Subdisplays
- High Speed Automatic Antenna Tuner
- DSP Noise Reduction

Download brochure below for all the specifications.



Article id:	YAESU FT-DX5000MP LTD	
Price:	€ 3599,00	ex VAT € 2974,38