

YAESU FTM-7250DE

VHF/UHF C4FM/FM MOBILE RADIO



This new Yaesu FTM-7250DE is a compact ruggedly built C4FM/FM 144/430MHz Dual Band 50W Transceiver incorporating the latest advanced features YAESU offers for the System Fusion II platform. Users can expect this attractive new transceiver to provide reliable performance for long-lasting communications because the FTM-7250DE incorporates a Heavy-Duty Heat Sink equipped with the Yaesu exclusive FACC (Funnel Air-Convection Conductor – Wind Tunnel). Its Front Speaker delivers 3W of powerful clear and crisp audio – ensuring consistent communications - even in noisy environments.

As with other YAESU C4FM Transceivers, the new FTM-7250DE supports the Automatic Mode Select (AMS) function (a front panel LED indicates the transceiver's mode of operation with the received signal indicated by Blue for digital C4FM or Green for analog FM), Digital Group ID (DG-ID)/ Digital Personal ID (DP-ID) features for group communications and easy connectivity to the WiRES-X Internet Linking System. A new feature of the FTM-7250DE is its expanded Wider Receiver Coverage: 108 – 579.995 MHz (108 – 137 MHz: Air Band).

The rear panel has a DATA jack for free firmware updates from the Yaesu website.

Other functions included in the new FTM-7250DE are a.o.:

- System Fusion-II Compatible
- Operates Advanced C4FM Digital and Conventional FM modes
- Large Multi-Color LED Indicator to show Operation Mode at glance
- True 50 Watts (VHF and UHF) Stable High-Power Transmitter with FACC
- High Stability ± 2.5 ppm TCXO Included
- 225 memories (199 "basic" memory channels, 10 sets of band-edge memory channels and 6 "Home" channel) with 8 character Alpha-numeric tags
- Keyboard entry of operating frequencies from the supplied DTMF microphone
- Built-in CTCSS and DCS Encoder/Decoder circuits
- Time-Out-Timer (TOT)
- Automatic Power-Off(APO)
- Automatic Repeater Shift (ARS)
- VFO scan
- Preferential Memory Scan
- Programmable memory scan
- Dual Watch

Technical Data

Frequency Ranges RX : 108 - 579.995MHz (108 - 137MHz : Airband)
Frequency Ranges TX : 144 - 146 MHz; 430 - 440 MHz (amateur bands only)
Circuit Type : Double-Conversion Superheterodyne
Modulation Type : F2D, F3D, F7W
RF Power Output : 50 W/25 W/5 W
Memory Channels : 225

Article id:	YAESU FTM-7250DE	
Price:	€ 269,00	ex VAT € 222,31



YAESU FTM-7250DE

VHF/UHF C4FM/FM MOBILE RADIO

Antenna socket : SO 239 (PL-female)

Case Size : W155 x H42 x D145.5 mm w/o Knob and Fan

Weight : Approx. 1.3kg

The FTM-7250DE is supplied with:

- MH-48A6JA DTMF microphone
- Mounting Bracket
- DC Power Cord
- USB cable
- Operating Manual

Article id: YAESU FTM-7250DE

Price: € 269,00

ex VAT € 222,31

Classic International B.V.

Zuidhoven 9 G

6042 PB Roermond

The Netherlands

info@classicinternational.eu

<https://www.classicinternational.eu>

Copyright © 2021 Classic International B.V.
Printing errors reserved

Date: 17-01-2021