

YAESU MD100A8X

DESK MICROPHONE



Dynamic desk microphone.

Specifications

Element : Dynamic
Frequency : 100 Hz - 6 kHz
Sensitivity : - 75 dB
Impedance : 500 Ohms
Dimensions : 112 x 156 x 151 mm
Weight : 670 g

Buttons : PTT, PTT-Lock, Up/Down, On/Off switch on the microphone
Filters : High-Emphasis + 2 x Low-Cut Off (-5 dB/100 Hz en -10 dB/100 Hz)
Connector : 8-pole round. Also to be used for RJ 45/modular*)
Pinning : Pin 1 - Up
: Pin 2 - +5V
: Pin 3 - Down
: Pin 4 - Fast
: Pin 5 - Ground
: Pin 6 - PTT
: Pin 7 - Mic Gnd
: Pin 8 - Mic

The MD-100A8X can be used with a.o.

- FT-840
- FT-847
- FT-857
- FT-897
- FT-990
- FT-950
- FT-1000(MP)
- FT-2000

*) The RJ45 and 8P sockets in the base of the MD-100 are internally connected 1:1. The supplied microphone cable has RJ45 on one side and an 8-pin round plug on the other. You can therefore use the cable for devices with RJ45 as well as for devices with an 8-pin round microphone plug. Simply reverse the cable.

Article id: YAESU MD100A8X

Price: € 129,00

ex VAT € 106,61