

# YAESU M-1

## DESK MICROPHONE

### 8 PIN ROUND/RJ 45



The top of the range Yaesu M-1 is a high-quality, innovative desktop microphone, designed for the discriminating operators.

It features combined condenser and dynamic microphone elements. The condenser microphone element produces greater frequency response and clear, crisp audio characteristics perfect for being heard in crowded bands and in big DX pile-ups. The dynamic microphone element delivers the rich low-mid tonalities, favored for local QSOs. The response of each microphone element may be adjusted independently using the internal nine band graphic equalizer. Each element has a separate volume control for independent adjustment of output levels. The output of each microphone may be selected separately, or they may be combined to produce the most pleasant tonality. Both the condenser element and dynamic element in the M-1 utilize the nine band graphic equalizer (63Hz, 125Hz, 250Hz, 500Hz, 1kHz, 2kHz, 4kHz, 8kHz, 16kHz). Each element's frequency response is independently adjustable. Two frequency response memories and a "through" mode are provided for each element, and are easily switchable by one-touch buttons on the microphone base.

The supplied Treble Boost Cowling enhances the voice response around the important 1 – 1.5 kHz range. Attaching the cowling creates a condensed unique tonal texture that is pleasing for many. The PTT key uses three air-cylinder tubes and features a contactless magnetic switch that ensures long-life and stable operation.

Other included features are:

- Recording and playback capability (20 seconds), to confirm the audio tonality
- Large red TX LED indicator
- Large graphic equalizer and frequency response scope LCD display with anti-reflective coating
- Headphone jack
- Touch PTT keylock
- Built-in low-cut filter to shape the low frequency response
- Cannon-type XLR output plug connector
- Audio output volume control for headphones
- Two screwdrivers are included to precisely adjust the graphic equalizer and microphone gains

Specifications

Microphone Type : Dynamic and Condenser  
Supply Voltage : DC 5,0 V  $\pm$  5%  
Frequency Response : 30-17000 Hz  
Sensitivity : -60 dB (1 kHz, 0 dB = 1 V/1 Pa)  
Microphone Impedance : 600 Ohms  
Headphone Impedance : 16 Ohms  
Headphone Output Level : 15 mW  
RX audio in (input level) : 100 mV rms



Article id: **YAESU M-1**

Price: **€ 629,00**

ex VAT € 519,83

# YAESU M-1

## DESK MICROPHONE

### 8 PIN ROUND/RJ 45

Dimensions : 140 x 280 x 152mm

Weight : 960 g (w/o cable)

The M-1 desktop microphone is supplied with:

- TBC (Treble Boost Cowling)
- Microphone cable
- AC Adapter
- Operating Manual (English)

The M-1 is compatible with:

- Yaesu FT-DX9000
- Yaesu FT-DX5000 series
- Yaesu FT-DX3000
- Yaesu FT-DX1200
- Yaesu FT-991(A)

**Article id:** YAESU M-1

**Price:** € 629,00

**ex VAT € 519,83**

Classic International B.V.

Zuidhoven 9 G

6042 PB Roermond

The Netherlands

[info@classicinternational.eu](mailto:info@classicinternational.eu)

<https://www.classicinternational.eu>

Copyright © 2021 Classic International B.V.  
Printing errors reserved

Date: 17-01-2021