

HIMUNICATION HM-380 DSC/GPS (ATIS)

VHF MARINE RADIO | 156-162 MHZ



The HIMUNICATION HM380 is a compact VHF marine radio, including ATIS.

On request we can program ATIS and MMSI data.

Features

- Slim model
- Quick heat dissipation
- Waterproof according to IP67 standard
- Channel 31 (NL) pre-programmed
- ATIS (can be programmed by us)
- LCD-Display with background light
- MOB Alert (Man Overboard)
- Connector for external speaker (3,5 mm)
- Real DSC-System
- GPS receiver; only operates with optional GPS Dongle or external NMEA0183 compatible GPS system

The large LCD with full dot-matrix display of the HIMUNICATION HM380 marine radio clearly shows all data and active functions.

Specifications

Frequency range TX : 156.025 - 157.425 MHz
 Frequency range RX : 156.050 - 162.025 MHz
 Kanalen : 57 internationale
 Mode : FM (16K0G3E) / DSC (16K0G2B)
 Waterproof : According to IP67 standaard
 ATIS : yes
 MMSI : yes
 Output power : High (HI) - 25 W | Low (LO) - 1W
 Scan function : yes
 Audio-output receiver : > 5 W @ 4 Ohm
 Squelch : yes
 Priority channel : yes, channel 9/16
 DSC-System – : yes
 Dual Watch Function : yes, to monitor channel 16 and current channel in cycle
 Triple Watch Function : yes, to monitor channel 16, current channel and one programmed channel in cycle
 Keys microphone : die most important functions can be chosen on the keypad of the microphone
 Connections : for external loudspeaker/GPS (3,5 mm Mono/GPS)
 Ambient temperature : -15°C to +55°C
 Power supply : 13,8 VDC
 Dimensions : H 114 x W 224 x D 50 mm (without mounting bracket)
 Weight : 1,5 kg (only radio)

The Himunication HM380 is supplied with:

- Microphone

Article id:	HIMUNICATION HM-380 DSC/GPS (ATIS)	
Price:	€ 239,00	ex VAT € 197,52



HIMUNICATION HM-380 DSC/GPS (ATIS)

VHF MARINE RADIO | 156-162 MHZ

- Microphone holder
- NMEA0183 connectors
- DC cable
- Mounting bracket with screws
- Manual English

Article id:	HIMUNICATION HM-380 DSC/GPS (ATIS)	
Price:	€ 239,00	ex VAT € 197,52